



ARCHIVED - Archiving Content

Archived Content

Information identified as archived is provided for reference, research or recordkeeping purposes. It is not subject to the Government of Canada Web Standards and has not been altered or updated since it was archived. Please contact us to request a format other than those available.

ARCHIVÉE - Contenu archivé

Contenu archivé

L'information dont il est indiqué qu'elle est archivée est fournie à des fins de référence, de recherche ou de tenue de documents. Elle n'est pas assujettie aux normes Web du gouvernement du Canada et elle n'a pas été modifiée ou mise à jour depuis son archivage. Pour obtenir cette information dans un autre format, veuillez communiquer avec nous.

This document is archival in nature and is intended for those who wish to consult archival documents made available from the collection of Public Safety Canada.

Some of these documents are available in only one official language. Translation, to be provided by Public Safety Canada, is available upon request.

Le présent document a une valeur archivistique et fait partie des documents d'archives rendus disponibles par Sécurité publique Canada à ceux qui souhaitent consulter ces documents issus de sa collection.

Certains de ces documents ne sont disponibles que dans une langue officielle. Sécurité publique Canada fournira une traduction sur demande.

TM-05-92

Radiation Measurements on Police Traffic Radar Speed Detectors

By D. Zaneite and D. Scribailo

TECHNICAL MEMORANDUM

Submitted by
MPB Technologies Inc.

February 1992

NOTE: Further information
about this report can be
obtained by calling the
CPRC information number
(613) 998-6343

Copyright of this document does not belong to the Crown.
Proper authorization must be obtained from the author for
any intended use.

Les droits d'auteur du présent document n'appartiennent
pas à l'État. Toute utilisation du contenu du présent
document doit être approuvée préalablement par l'auteur.

Executive Summary

The safe use of police traffic radar units has raised a number of questions in the community. As a result, the Ottawa Police approached the Canadian company MPB Technologies to do a study on "Radiation Measurements on the Police Traffic Radar Speed Detectors". All submitted units were well within Canada's National Health and Welfare, "Safety Code-6" designation.

- Note 1 Actual measurement data sheets are not included in this report but will be supplied on request.
- Note 2 : The following sections are not included, Section 3 - Calibration Certificates, Appendix A - Power Density Table, Appendix B - Radiation Patterns, Appendix C - Test Equipment Report.
- Note 3 : Appendix D - Bibliography is included.

Customer No.: 70670

MPBT No.: 1126

Test Report for
Radiation Measurements
on the
Police Traffic Radar
Speed Detectors

L. Allan


Prepared for:

OTTAWA POLICE
474 Elgin Street
Ottawa, Ontario
K2P 2J6

Prepared by:

MPB Technologies Inc.
Building M-50, NRC
Montreal Road
Ottawa, Ontario
K1A 0R6

November 26, 1991
03-R-126(MS)



Dave G. Scribailo
Manager
Electromagnetic Services
Electromagnetics Division

TABLE OF CONTENTS

1.0 Summary of Radar Measurements

2.0 Radar Measurements

3.0 Calibration Certificates

APPENDICES

Appendix A: Power Density Table

Appendix B: Radiation Patterns

Appendix C: Test Equipment Report

Appendix D: Bibliography

1.0 SUMMARY OF RADAR MEASUREMENTS



SUMMARY

The Safety Code - 6 of National Health and Welfare states that the "General Public (those individuals that are not microwave radiation workers) shall not be exposed to power density levels greater than one (1) mW/cm^2 averaged over a one-minute period in the range of frequencies between 10 MHz and 300 GHz.

Units #30 (13299) and #28 (13301) operate on CW (continuous wave) and are well below the one (1) mW/cm^2 .

The remaining units operate on a 40% duty cycle. The radiated power would be 40% of the measured value with a possible error of +20% -17%.

All units passed, with #12 (6659) being borderline at two (2) inches.

$$\text{ie: } 2.14 \text{ mW}/\text{cm}^2 \cdot 40\% \cdot 120\% = 1.0 \text{ mW}$$

2.0 RADAR MEASUREMENTS

OTTAWA POLICE RADAR SPEED DETECTORS

The radiation levels at 10.524 GHz were checked at two (2) and six (6) inches from the horn cover.

A small linear horn (2.5 cm x 2.25 cm mouth) was used to receive the radiated energy. The Horn was first calibrated, using an HP8510 Network Analyzer. With the three-antenna system, the gain of the Horn measured 9 dB. The expected power from the Horn in a 1-mW/cm² field was determined by the formula:

$$Pr = \frac{F \cdot G \cdot \lambda^2}{4 \pi}$$

Pr = Power Received

F = Field mW/cm² at the Horn focus

G = Gain of Horn

λ = Wavelength at 10.524 GHz

$$\text{ie: } Pr = \frac{1 \text{ mW/cm}^2 \times 9 \times (2.849\text{cm})^2}{4 \pi} = 5.8 \text{ mW}$$

A calibrated source of 10.524 GHz was set to 5.8 mW and fed into a receiver. The Receiver signal was noted and compared to the signals from the Horn when the Horn was placed two (2) and six (6) inches from the radars. Since the radars transmit circular polarized signals, the vertical and horizontal signal from the Horn were added. The results and shown in Table 1.

Note 1:

For measurements, all radars were set to CW operation. If the radars are modulated OFF and ON, the average radiation power will be reduced in the same ratio as of the ON and OFF time.

Note 2:

The overall -accuracy of the measurement was + 0.8 dB or +20% -17%.

Note 3:

Some radiation patterns have been included for general information.

BIBLIOGRAPHY

- NBS: Technical Note 1319,
"Generation of Standard Electromagnetic Fields in a TEM Cell".
Ref: Kank+, M.; Orr, R. David
- NRCC: "Measurement of Antenna Factors with a TEM cell",
Ref: Kashyap, S.C.
- ECSM: **The Equivalent Capacitance Substitution Method",**
Ref, Jordan, E.C., "EM Waves & Radiating System",
p. 483
Ref: Navship 94810, "The Radio Freq. Interference
Meter", Univ. of Penn., 1962,
Para. 12.4.1
- IEEE 3024969 "The Institute of Electrical & Electronic Engineers",
sect. 2.2.2.3
- NBS: Technical Note 1309, 1987
"Calibration Procedures for Horizontal Dipole Antennas
(25 to 1000 MHz)",
Ref: Camell, D.G.;Larsen, E.B.; Cruz, J E .
- ANSI C63.5: "American National Standards for Electromagnetic
**Compatibility, Radiated Emission Measurement in EMI,
Calibration of Antennas",**
1988
- SAE-ARP 958: "Broadband Electromagnetic Interference Measurement
Antennas; Standard Calibration Requirements &
Methods
- SAFETY CODE - 6 "Recommended Safety Procedures for the Installation
and Use of Radiofrequency & Microwave Devices in
the Frequency Range 100 MHz - 300 GHz",
Environmental Health Directorate,
Health Protection Branch,
1979